

HI-PRO (IP-72010) **OUTRIGGER PAD**

Our Hi-Pro outrigger pads offer complete protection when working on high value flooring with their non-marking rubber base. They are also hi-viz yellow for working in pedestrianised areas.

- Engineered from High Density Polyethylene (HDPE)
- Non-marking rubber base
- Tough and stable support for outrigger legs
- Resistant to water, oil and chemicals
- Lightweight and easy to handle



MATERIAL SPECIFICATION		
PROPERTIES	TEST METHOD	TEST RESULTS
Physical Properties		
Density	ASTM D-792	0.937-0.98 g/cm ³
Water Absorption	ASTM D-570(2)	< 0.01%
Upper Temperature Limit	-	90°C
Lower Temperature Limit	-	-269°C
Mechanical Properties		
Tensile Strength at Yield	ASTM D-638	>17 MPa
Tensile Strength at Break	ASTM D-638	>35 MPa
Elongation at Yield	ASTM D-638	12%
Ultimate Elongation	ASTM D-638 / ISO527	>350% / >400 %
Tensile Modulus	ASTM D-638	820 MPa
Izod impact, Notched	ASTM D-256 Type A	No break KJ/m ²
Flexural Strength	ASTM D-790	26 MPa
Flexural Modulus	ASTM D-790	760 MPa
Compression Strength (10%Def)	ASTM D-695	27 MPa
Compressive Modulus	ASTM D-695	550 MPa
Hardens (Shore D Hardness)	ASTM D-2240	60-70 Shore D
Static Friction Coefficient	ASTM D-1894	0.11-0.17
Dynamix Friction Coefficient	ASTM D-1894	0.7-0.11
Thermal Properties		
Coefficient of Linear Expansion	ASTM D-696	1.5 10 ^{-₄} /ºC
Thermal Conductivity @23'C	ASTM D-177	0.4W/m.k
Specific Heat @ 23'C	ASTM E-1269	0.48 Cal/gºC
Electrical Properties		
Volume Resistivity	ASTM D-257	>10 ¹⁴ Ohm.cm
Surface Resistivity	ASTM D-257	>1012 Ohm
Dielectric Constant @1MHZ	ASTM D-150	2.3

Product Code: IP-72010 Dimensions (mm): 400 x 400 x 40 Load Capacity (tonnes): 12.00 Weight (kgs): 6.00 Recess Size (mm): 300 x 10 Material: HDPE



The data mentioned in this brochure are average values ascertained by current statistical returns and tests, but we cannot accept any responsibility for their accuracy.



TECHNICAL ADVICE





T +44 (0)1952 671403 E sales@outriggerpads.co.uk outriggerpads.co.uk

BE CONFIDENT. BUY QUALITY.

