



# ECO LIFT (IP-72015) OUTRIGGER PAD

These Eco Lift Pads provide strong and stable support to help with load distribution. They are perfect for use with small to medium sized equipment.

- **Engineered from High Molecular Weight Polyethylene (HMW-PE)**
- **Tough and stable support for outrigger legs**
- **Resistant to water, oil and chemicals**
- **Lightweight and easy to handle**
- **Can be carried, positioned and stored with minimal effort**

## SUITABLE FOR:



## MATERIAL SPECIFICATION

PROPERTY	VALUE	TEST METHOD
Density	0.93-0.955g/cm <sup>3</sup>	ASTM D1505
Melting point	133-135°C	ASTM D3418
Tensile strength at yield	23-26MPa	IOS 527:2012
Tensile strength at break	14-16MPa	ISO 527:2012
Elongation at break	80-100%	ISO 527:2012
Elasticity modulus	1100-1210MPa	ISO 527:2012
Charpy impact strength - notched	33-37KJ/m <sup>2</sup>	ISO 179-1:2011
Hardness	67-69 SHORE D	ISO 868:2003
Wear resistance sand-slurry-test	372%	ISO 15527
Average coeff. of linear thermal expansion	2x10 <sup>-4</sup> m/(m/K)	-
Service temperature	-100 to 80°C	-

The data mentioned in this brochure are average values ascertained by current statistical returns and tests, but we cannot accept any responsibility for their accuracy.

Product Code: **IP-72015**

Dimensions (mm): **400 x 400 x 40**

Material: **HMW-PE**

Load Capacity (tonnes): **12.00**

Weight (kgs): **6.00**

Recess Size (mm): **300 x 8**



TECHNICAL  
ADVICE



EASY  
ORDERING



NEXT DAY  
DELIVERY  
Order by 4pm

BE CONFIDENT. BUY QUALITY.

