



HI-VIZ (IP-72042) OUTRIGGER PAD

These bright yellow pads are commonly used in public areas such as, parking bays, shopping centres, pavements, roadsides and pedestrianised walkways... but can be used in any application where potential trip hazards may occur.

- Alerts pedestrians to potential trip hazards
- Provides greater visibility in poor light or muddy ground conditions
- Tough and stable support for outrigger legs
- Engineered from High Molecular Weight Polyethylene (HMW-PE)
- Resistant to water, oil and chemicals
- Lightweight and easy to handle

SUITABLE FOR:



MATERIAL SPECIFICATION

PROPERTY	VALUE	TEST METHOD
Density	0.93-0.955g/cm ³	ASTM D1505
Melting point	133-135°C	ASTM D3418
Tensile strength at yield	23-26MPa	IOS 527:2012
Tensile strength at break	14-16MPa	ISO 527:2012
Elongation at break	80-100%	ISO 527:2012
Elasticity modulus	1100-1210MPa	ISO 527:2012
Charpy impact strength - notched	33-37KJ/m ²	ISO 179-1:2011
Hardness	67-69 SHORE D	ISO 868:2003
Wear resistance sand-slurry-test	372%	ISO 15527
Average coeff. of linear thermal expansion	2x10-4m/(m/K)	-
Service temperature	-100 to 80°C	-

The data mentioned in this brochure are average values ascertained by current statistical returns and tests, but we cannot accept any responsibility for their accuracy.

Product Code: **IP-72042**

Dimensions (mm): **400 x 400 x40**

Material: **HMW-PE**

Load Capacity (tonnes): **12.00**

Weight (kgs): **6.14**

Recess Size (mm): **300 x 10**



TECHNICAL
ADVICE



EASY
ORDERING



NEXT DAY
DELIVERY
Order by 2pm

BE CONFIDENT. BUY QUALITY.



T +44 (0)1952 671403 E sales@outriggerpads.co.uk outriggerpads.co.uk