



- Large scale crane lifting
- Reduces overall pressure
- Quick and easy to set up

## MULTI MAT SYSTEM



RELIABLE. STRONG. SAFE.



[outriggerpads.co.uk](http://outriggerpads.co.uk)

# MULTI MAT SYSTEM GUIDE



Manufactured to our premium pad specification our multi-mat system offers the perfect solution for large scale crane lifting. Excellent durability and rigidity reduces the overall pressure directed at the ground effectively supporting the equipment.

## MULTI MAT SET-UP

**Stage 1** - Three mats are laid side by side

**Stage 2** - Two mats are placed on top at 90 degrees

**Stage 3** - A single outrigger pad is placed centrally on the top, securing the multi mat system

**Please note:** Ensure there are no gaps or debris present in the set-up. If in doubt refer to your lift plan.

## Multi Mat Options

**IP-57709**  
1500x500x50mm

**IP-57710**  
1800x600x50mm

**IP-57683**  
1000x60mm

**IP-57685**  
1200x60mm

Our Multi Mat system recommends a round pad to secure, but a square pad is equally suitable.

Dimensions (mm)	Weight (kgs)	Product Code
1500x500x50	36.00	IP-57709
1800x600x50	54.00	IP-57710
1000x60 (to secure)	45.00	IP-57683
1200x60 (to secure)	66.40	IP-57685



## Configuration Options

1500x500x50mm

**75 TONNES**

**1.50m<sup>2</sup> Configuration**  
Requires:  
IP-57709 x 2  
IP-57683

**100 TONNES**

**2.25m<sup>2</sup> Configuration**  
Requires:  
IP-57709 x 5  
IP-57683

**110 TONNES**

**3m<sup>2</sup> Configuration**  
Requires:  
IP-57709 x 7  
IP-57685

1800x600x50mm

**100 TONNES**

**2.16m<sup>2</sup> Configuration**  
Requires:  
IP-57710 x 2  
IP-57685

**140 TONNES**

**3.24m<sup>2</sup> Configuration**  
Requires:  
IP-57710 x 5  
IP-57685

**160 TONNES**

**4.32m<sup>2</sup> Configuration**  
Requires:  
IP-57710 x 7  
IP-57685

**Please note:** Capacity based on complete Multi Mat system. These configurations are calculated for the max ground pressure of 5kgs/cm<sup>2</sup>, for normal operational conditions.