



ECO LIFT OUTRIGGER PADS

Long-lasting performance, strength and stability. Eco Lift outrigger pads offer excellent load distribution for small to medium-sized equipment.

- **Engineered from High Molecular Weight Polyethylene (HMW-PE)**
- **Resistant to water, oil & chemicals**
- **Lightweight and easy to handle**

SUITABLE FOR:



MATERIAL SPECIFICATION

PROPERTIES	UNIT	TEST METHOD
Density	0.93-0.955g/cm ³	ASTM D1505
Melting point	133-135°C	ASTM D3418
Tensile strength at yield	23-26MPa	IOS 527:2012
Tensile strength at break	14-16MPa	ISO 527:2012
Elongation at break	80-100%	ISO 527:2012
Elasticity modulus	1100-1210MPa	ISO 527:2012
Charpy impact strength - notched	33-37KJ/m ²	ISO 179-1:2011
Hardness	67-69 SHORE D	ISO 868:2003
Wear resistance sand-slurry-test	372%	ISO 15527
Average coeff. of linear thermal expansion	2x10 ⁻⁴ m/(m/K)	-
Service temperature	-100 to 80°C	-

Product Code: **IP-72088**

Dimensions (mm): **450x450x40**

Recess size (mm): **N/A**

Material: **HMW-PE**

Load Capacity (tonnes) **14**

Weight (kgs): **8.10**



The data mentioned in this leaflet are average values ascertained by current statistical returns & tests, but we cannot accept any responsibility for their accuracy.



**TECHNICAL
ADVICE**



**EASY
ORDERING**



**NEXT DAY
DELIVERY**
Order by 2pm

BE CONFIDENT. BUY QUALITY.

