

DATA SHEET

ETHAFOAM SURFACE SHEETS

Designed to be used under outrigger pads, our Ethafoam surface sheets are ideal for reducing uneven surfaces and protecting block paving and cobble stones from damage.

- Made from low density foam, it cushions and protects against repeated impact
- A great alternative to sand, as it can be reused over and over again
- Resistant to water, oil & chemicals
- Lightweight and easy to handle
- Carry, position and store with minimal effort



SUITABLE FOR:



MATERIAL SPECIFICATION

DESCRIPTION	STANDARD	VALUE	UNIT
Density	DIN 53420	24	Kg/m ³
Tensile strength: extrusion direction	DIN 53571	0.219	N/mm ²
Tensile strength: cross direction	DIN 53571	0.170	N/mm ²
Elongation at break: extrusion direction	DIN 53571	67	%
Elongation at break: cross direction	DIN 53571	52	%
Compression strength 25% (4th compression)	DIN 53577	0.024	N/mm ²
Compression strength 50% (4th compression)	DIN 53577	0.081	N/mm ²
Compression strength 70% (4th compression)	DIN 53577	0.200	N/mm ²
Thermal stability (24 hours at 70°C)	ASTM D-3575-S	<0.5	%
Cell size	BS 4443/1 Met.4	>20	Cells/25mm
Water absorption after 24 hours	DIN 53428	1.19	Vol %
Working temperature range	Internal	-30 to +80	°C

Product Code: IP-72193

Dimensions (mm): **2000x700x25**

Material: **STPE200 Polyethylene Foam**

Weight (kgs): **1.80**



The data mentioned in this leaflet are average values ascertained by current statistical returns & tests, but we cannot accept any responsibility for their accuracy.



**TECHNICAL
ADVICE**



**EASY
ORDERING**



**NEXT DAY
DELIVERY**
Order by 2pm

BE CONFIDENT. BUY QUALITY.



T +44 (0)1952 671403 E sales@outriggerpads.co.uk outriggerpads.co.uk